## **Rimage 2000i Specifications**

This document provides product specification information for the Rimage 2000i autoloader. For more information on how to operate and identify the parts of the Rimage 2000i, refer to the *Rimage 2000i User Guide*.

## **Notes:**

- The most up-to-date 2000i specification information is found in the current revision of this document.
- 480i printer specifications as well as other manuals referenced in this document are available at www.rimage.com/support. From the Support menu select: *Product Series > Product Name >* User Manuals tab.

	Rimage 2000i	
Standard system	The standard system includes the Rimage 2000i autoloader (with the integrated Rimage 480i printer assembly) and Rimage 2000i Software.	
Number of recorders	2 CD/DVD combination recorders	
Bin capacity		
Supply bin	100 discs	
Output bin	100 discs	
Physical size		
Height	21.0 in (53.3 cm)	
Width	15.8 in (40.0 cm)	
Depth*	20.0 in (50.8 cm)	
Weight	62.0 lb (28.1 kg)	
Software requirements	The Rimage 2000i ships with Rimage 2000i Software™. The Rimage 2000i operates with either Rimage 2000i Software or Rimage OfficeNET™ Software Suite. To purchase OfficeNET Software Suite, contact your Rimage reseller.	
Media requirements	Use only 120 mm optical discs that are coated with an ink-jet printable surface. The media in Rimage Media Kits™ are designed for optimum print performance. Learn more about Rimage Media Kits™ at www.rimage.com.	
Power	100 - 240 VAC, 60/50 Hz, 2.7 Amps	

<sup>\*</sup>Leave an additional 3.5 in (9 cm) for cabling.

	Rimage 2000i		
Minimum PC requirements	! Important! If you do not understand these requirements, ask your computer technician for help or refer to your PC documentation.		
Supported	32-bit platform support:	64-bit platform support *:	
operating systems	Windows XP® Professional SP3	Windows 7 Ultimate, Enterprise, and	
	<ul> <li>Windows Vista Business, Enterprise, and Ultimate edition with SP2</li> </ul>	<ul> <li>Professional</li> <li>Windows Vista Business, Enterprise, and Ultimate edition with SP2</li> </ul>	
	Windows 7 Ultimate, Enterprise, and Professional		
	Note: Server OS is not supported	Note: Server OS is not supported	
Processor	Dual core processor Minimum   Core i3 or i5 Recommended		
RAM/Memory	2 GB Minimum   4GB Recommended		
Ports	Use an integrated high-speed USB 2.0 port (using a USB expansion card is not recommended)		
Fixed storage	Minimum - Two 7,200 RPM hard drives with 200 GB free space on each drive Recommended- Two 7,200 RPM HDDs configured as Raid0 w/400GB of free space		
Removable storage	One CD/DVD-ROM		
Graphics	1024 x 768 screen resolution, 32-bit color		
Networking ability	Yes, when using OfficeNet Software Suite. Refer to the <i>Rimage Advanced Setup</i> (Networking) Guide at www.rimage.com/support for instructions on submitting orders from a networked computer.		
Print quality			
Technology	Thermal inkjet printing with separate color and black cartridges		
Resolution	Up to 4800 dpi		
Droplet size	3 pico-liters		
Pixel density	5.76 million pixels per square inch		
Temperature and humidity			
Operating temperature	60° to 95° F (16° to 35° C)		
Humidity	40% to 80% non-condensing		
Storage temperature	5° to 95° F (-15° to 35° C)		

<sup>\*</sup>New in Rimage software version 8.5.